# Part Number: TF24-CM4-PLO900 - 2
# 24 Strand, TiniFiber® Micro Armor™ +Steel Braid, Corning Multimode OM4 50/125, 900 µm Tight Buffer, PVC, Plenum UV, Black, Indoor/ Outdoor Premise, Duct, Conduits, and Patch




## General Specifications

| | |
|---|---|
| **P/N** | TF24-CM4-PLO900 - 2 |
| **Application and Uses** | Indoor Outdoor Premise, Duct, Conduits, and Patch |
| **Outer Jacket Specifications / Color** | PLENUM-UV \| BLACK |
| **Fiber Category** | Multimode OM4 50/125 |
| **Fiber Type** | |
| **Fiber Count / Grouping** | 24 Strand \| 1x24f |
| **Construction** | |
| **Maximum Attenuation** | ≤3.0 dB/km @ 850 nm \| ≤1.5 dB/km @1300 nm |
| **Core/Cladding** | |
| **Water Block** | Yes |
| **Armor** | TiniFiber® Micro Armor™ +Steel Braid |
| **Maximum Tensile Strength (Dynamic \| Static)** | 700 N \| 300 N |
| **Maximum Crush Resistance (Dynamic \| Static)** | 20 kN/m \| 5 kN/m |
| **Minimum Bend Radius (Dynamic \| Static)** | 20D \| 10D |
| **Nominal Outer Diameter** | 11.0±0.5 mm |
| **Cable Weight** | 145 kg/km (~97 lbs/kft) |
| **Installation Temperature** | -10 to 60 °C (14 to 140 °F) |
| **Operation Temperature** | -15 to 60 °C (5 to 140 °F) |
| **Storage Temperature** | -15 to 60 °C (5 to 140 °F) |



1180 ROUTE 109 | Lindenhurst, NY 11757 | 1(800)-396-0142 | sales@tinifiber.com

| | |
|---|---|
| **Standards** | Telcordia GR-20, TIA-568.3, ICEA-S-104-696 |
| **Conductor Count** | |
| **Conductor Gauge** | |
| **Conductor Type** | |
| **Conductor Outer Jacket Material** | |
| **Conductor Color Code** | |
| **Patent Number** | https://tinifiber.com/patent-notices |



1180 ROUTE 109 | Lindenhurst, NY 11757 | 1(800)-396-0142 | sales@tinifiber.com