Part Number: TF2Z-OM1-PU3.0 - 2
2 Strand / Zip, TiniFiber® Micro Armor™, Multimode OM1 62.5/125, Thermoplastic Polyurethane, BLACK, Tactical Outdoor Premise, Duct, Conduits, and Patch



General Specifications

P/N	TF2Z-OM1-PU3.0 - 2
Application and Uses	Tactical Outdoor Premise, Duct, Conduits, and Patch
Outer Jacket Specifications / Color	Thermoplastic Polyurethane | BLACK
Fiber Category	Multimode OM1 62.5/125
Fiber Type	
Fiber Count / Grouping	2 Strand / Zip
Construction	
Maximum Attenuation	3.5 dB/km @ 850 nm | 1.5 dB/km @ 1300 nm
Core/Cladding	
Water Block	Yes
Armor	TiniFiber® Micro Armor™
Maximum Tensile Strength (Dynamic | Static)	225 N | 135 N
Maximum Crush Resistance (Dynamic | Static)	30 kN/m | 10 kN/m
Minimum Bend Radius (Dynamic | Static)	20D | 10D
Nominal Outer Diameter	2.8-2.95*5.7±0.2mm
Cable Weight	24 kg/km (~16 lbs/kft)
Installation Temperature	-30 to 60 °C (-22 to 140 °F)
Operation Temperature	-40 to 70 °C (-40 to 158°F)
Storage Temperature	-40 to 70 °C (-40 to 158°F)

1180 ROUTE 109 | Lindenhurst, NY 11757 | 1(800)-396-0142 | sales@tinifiber.com

Standards	Telcordia GR-20, TIA-568.3, ICEA-S-104-696
Conductor Count	
Conductor Gauge	
Conductor Type	
Conductor Outer Jacket Material	
Conductor Color Code	
Patent Number	https://tinifiber.com/patent-notices

1180 ROUTE 109 | Lindenhurst, NY 11757 | 1(800)-396-0142 | sales@tinifiber.com