


Part Number: TF48-OS2-PVC
48 Strand 4x12f 250 µm Sub-unitized
Singlemode OS2 9/125 TiniFiber® Micro
Aarmor™ + Steel Braid YELLOW RISER
(PVC) Indoor Premise, Duct, Conduits, and
Patch



General Specifications

P/N	TF48-OS2-PVC
Application and Uses	Indoor Premise, Duct, Conduits, and Patch
Outer Jacket Specifications / Color	RISER (PVC) YELLOW
Fiber Category	Singlemode OS2 9/125
Fiber Count / Grouping	48 Strand 4x12f
Construction	250 µm Sub-unitized
Maximum Attenuation	0.4 dB/km @ 1310 nm 0.3 dB/km @ 1550 nm
Water Block	No
Maximum Tensile Strength (Dynamic Static)	1400 N 700 N
Maximum Crush Resistance (Dynamic Static)	30 kN/m 8 kN/m
Minimum Bend Radius (Dynamic Static)	20D 10D
Nominal Outer Diameter	10.5±0.5 mm
Cable Weight	130.5 kg/km (~88 lbs/kft)
Installation Temperature	0 to 60 °C (32 to 140 °F)
Operation Temperature	-15 to 60 °C (5 to 140 °F)