Part Number: TFH60-36OS2-24OM1-PLO - 2
60 Strand, 5x12f, TiniFiber® Micro Armor™ + Steel Braid, Singlemode OS2, Multimode OM1, PLENUM-UV, BLACK, Plenum, Indoor Outdoor Premise, Duct, Conduits, and Patch



General Specifications

P/N	TFH60-36OS2-24OM1-PLO - 2
Application and Uses	Indoor Outdoor Premise, Duct, Conduits, and Patch
Outer Jacket Specifications / Color	PLENUM-UV | BLACK
Fiber Category	Singlemode OS2 | Multimode OM1
Fiber Type	
Fiber Count / Grouping	60 Strand | 5x12f
Construction	
Maximum Attenuation	≤0.36 dB/KM @ 1310nm |≤0.23 dB/KM @ 1550nm / 3.5 dB/km @ 850 nm | 1.5 dB/km @ 1300 nm
Core/Cladding	
Water Block	Yes
Armor	TiniFiber® Micro Armor™ + Steel Braid
Maximum Tensile Strength (Dynamic | Static)	800 N | 600 N
Maximum Crush Resistance (Dynamic | Static)	20 kN/m | 6 kN/m
Minimum Bend Radius (Dynamic | Static)	20D | 10D
Nominal Outer Diameter	10.9±0.5 mm
Cable Weight	139 kg/km (~ 94 lbs/kft)
Installation Temperature	-10 to 60 °C (14 to 140 °F)
Operation Temperature	-15 to 60 °C (5 to 140 °F)

1180 ROUTE 109 | Lindenhurst, NY 11757 | 1(800)-396-0142 | sales@tinifiber.com

Storage Temperature	-15 to 60 °C (5 to 140 °F)
Standards	Telcordia GR-20, TIA-568.3, ICEA-S-104-696
Conductor Count	
Conductor Gauge	
Conductor Type	
Conductor Outer Jacket Material	
Conductor Color Code	
Patent Number	https://tinifiber.com/patent-notices

1180 ROUTE 109 | Lindenhurst, NY 11757 | 1(800)-396-0142 | sales@tinifiber.com