


## Micro Armor Fiber™ The Original Stainless Steel Armor Single Mode 2 Fiber Duplex OSP/Outdoor Armored Polyethylene Fiber Optic Cable Model #TF2-OS2-PL

TiniFiber® is a revolutionary designed fiber optic cable that will provide the single best solution for all your fiber optic projects and usage. Micro Armor Fiber™ can be used in any application: Telco, CATV, LAN, SAN, Broadcast, DAS, Communication, Security, Indoor, Outdoor as well as Aerial installations.



**Outer Jacket**  
 Material: PE  
 Color: Black  
 Outer Diameter: 3.0 mm



**2\*0.6mm Tight-Buffered Fiber,**  
**Kevlar, Steeltube, Water Block**  
**Yarn, Outer Jacket (Black)**  
 UL/OFC

### TiniFiber® Micro Armor Fiber™ Key Features

Feature	Benefits
<b>Micro Armor Fiber™</b>	1. The smallest OD of any armor compared to conventional optical fiber cable in size and flexibility 2. Lightest and smallest armor makes routing and installation faster and easier 3. Cables are up to 65% smaller and 75% lighter than conventional Aluminum Interlocking Armor (AIA)
<b>Encased Stainless Steel Coiled Tubular Armor</b>	1. Provides the strongest armor with smallest bend radius and designed for all indoor & outdoor conditions 2. Crush and rodent resistance
<b>Outer Jackets</b>	1. All jackets and colors for Riser, Plenum, Indoor/Outdoor, LSZH, Burial & Industrial projects
<b>Multimode/Single Mode Fibers</b>	1. OS2, OM1, OM3, OM4 from 1 to 144 Fibers (250m/900m/Ribbon) 2. Available in all standard connectors
<b>Kevlar</b>	1. Adds tensile strength and flexibility

### Competitive Product Analysis

Feature	Micro Armor Fiber™	Aluminum Interlock Armor (AIA)	Conventional Fiber Cable Jacket
Small Bend Radius	✓		✓
Smallest OD With Armor	✓		
Lightest Armor	✓		
Strongest Armor	✓	✓	
Lowest Installation Cost	✓		✓

## Micro Armor Fiber™ The Original Stainless Steel Armor Single Mode 2 Fiber Duplex OSP/Outdoor Armored Polyethylene Fiber Optic Cable Model #TF2-OS2-PL

**Common Installations:** Ducts, conduits, riser, and outdoor when installed according to NEC® Article 770  
**Design and Test Criteria:** ANSI/ICEA S-87-640



### General Specifications

Application	Outdoor Premise, Duct, Conduits, Riser and Patch
Fiber Category	Single Mode (OS2)
Fiber	Clear Curve Bend Insensitive
Storage	-40 °C to 80 °C (-40 °F to 176 °F)
Installation	-30 °C to 80 °C (-22 °F to 176 °F)
Operation	-40 °C to 80 °C (-40 °F to 176 °F)
Max. Dynamic Tensile Strength	200 N
Max. Static Tensile Strength	100 N
Max. Dynamic Crush Resistance	5000 N
Max. Static Crush Resistance	3000 N
Min. Dynamic Bend Radius	110 mm/ 4.3 in
Min. Static Bend Radius	55 mm/ 2.2 in
Nominal Outer Diameter	3.0 mm
Weight	13 kg/km
Stainless Steel Tube Outer Diameter	1.8 mm
Stainless Steel Tube Inner Diameter	1.25 mm
Wavelengths/Max. Attenuation	1310   ≤ 0.35dB/km   1550   ≤ 0.25dB/km
Fiber core/cladding diameter	9/125 mm
Fiber Count	2
Water Block	Dry Block Tape
Kevlar	3x1000dtex
Maximum Data Rate	Up to 100 GB
NEC Rating	OFC